

BRAZORIA COUNTY CONTRACT SHEETS

TABLE OF CONTENTS

ITB #16-59 SUPPLY AND INSTALLATION OF CARPET & FLOORING

TERM: JULY 26, 2016 – JULY 25, 2018

SUPPLY AND INSTALLATION OF CARPET AND FLOORING	2
SUPPLY AND INSTALLATION OF CARPET AND FLOORING (CONTINUED).....	3
SUPPLY AND INSTALLATION OF CARPET AND FLOORING (CONTINUED).....	4
PRODUCT SPECIFICATIONS FOR CARPET	4
PRODUCT SPECIFICATIONS FOR VINYL	5
ROPPE RUBBER STAIR TREAD SPECIFICATIONS.....	6
ROPPE RUBBER LANDING TILE SPECIFICATIONS.....	6
ROPPE 700 SERIES THERMOPLASTIC RUBBER BASR OR EQUIVALENT.....	6
ADHESIVE	7
MISCELLANEOUS INSTRUCTIONS.....	7

CONTRACT RELEASE

BRAZORIA COUNTY CONTRACT SHEETS

SUPPLY AND INSTALLATION OF CARPET AND FLOORING

ITB #16-59 SUPPLY AND INSTALLATION OF CARPET & FLOORING

	VENDOR	MAINLAND CARPET, INC.		
	ADDRESS	12865 HWY 6		
	CITY, STATE, ZIP	SANTA FE, TX 77510		
	CONTACT	RONNY TURRENTINE		
	QUOTED BY	RONNY TURRENTINE		
	TELEPHONE	409-925-2520		
	FAX	409-925-9880		
DESCRIPTION	UOM	QTY < 100 CARTONS < (4,800 SQ. FT.) COUNTY ID: 8194 PRICE	QTY ≥ 100 CARTONS ≥ (4,800 SQ. FT.) COUNTY ID: 8195 PRICE	
1.0 Homeroom II 26 Modular, Patcraft 26 oz. Commercial Carpet Tile 2'X2' Installed or Equivalent	SQ. FT.	\$3.10	\$3.00	
DESCRIPTION	UOM	QTY < 133 YRD COUNTY ID: 6819 PRICE	QTY ≥ 133 YRD COUNTY ID: 6818 PRICE	
1.0 Homeroom II 2802, Patcraft 28 oz. Commercial Carpet roll, 12' wide Installed or Equivalent	YD	\$18.99	\$17.82	
DESCRIPTION	UOM	QTY < 100 CARTONS < (4500 SQ. FT.) COUNTY ID: 6822	QTY ≥ 100 CARTONS (4500 SQ. FT.) TO 329 CARTONS (14,805 SQ. FT.) COUNTY ID: 6821	QTY ≥ 330 CARTONS ≥ (14,850 SQ. FT.) COUNTY ID: 6820
2.0 Armstrong Excelon VCT 12 x 12 x 1/8" Vinyl Commercial Flooring Installed or Equivalent	SQ. FT	\$1.40	\$1.30	\$1.10
DESCRIPTION	UOM	QTY < 100 CARTONS < (4500 SQ. FT.) COUNTY ID: 8196	QTY ≥ 100 CARTONS (4500 SQ. FT.) TO 329 CARTONS (14,805 SQ. FT.) COUNTY ID: 8197	QTY ≥ 330 CARTONS ≥ (14,850 SQ. FT.) COUNTY ID: 8198
2.0 Azrock VET 12x 12 x 1/8" Vinyl Commercial Flooring or Equivalent, Installed (45 SQ. FT. per Carton)	SQ. FT	\$3.00	\$2.95	\$2.85

BRAZORIA COUNTY CONTRACT SHEETS

SUPPLY AND INSTALLATION OF CARPET AND FLOORING (CONTINUED)

	VENDOR	MAINLAND CARPET, INC.		
	ADDRESS	12865 HWY 6		
	CITY, STATE, ZIP	SANTA FE, TX 77510		
	CONTACT	RONNY TURRENTINE		
	QUOTED BY	RONNY TURRENTINE		
	TELEPHONE	409-925-2520		
	FAX	409-925-9880		
DESCRIPTION	UOM	QTY <1,000 LINEAR FEET COUNTY ID:6824	QTY ≥1,000 LINEAR FEET COUNTY ID: 6823	
3.0 Roppe 700 Series Rubber Base Installed or Equivalent	Linear Feet	\$1.35	\$1.30	
DESCRIPTION	UOM	PRICE PER LINEAR FOOT COUNTY ID: 6825		
4.0 Roppe Rubber Stair Treads, Raised, Circular Vantage Design Installed or Equivalent	PRICE / Linear Feet	\$21.75		
DESCRIPTION	UOM	PRICE PER LINEAR FOOT COUNTY ID: 6826		
4.0 Roppe Rubber Landing Tiles, 996 Raised, Circular Vantage Design Installed or Equivalent	PRICE / SQ. FT.	\$11.40		
5.0 Additional floor preparation and floating:		PRICE PER BAG		
Cost per installed bag of Ardex brand SD-F (10 lb. bag) feather float or equivalent COUNTY ID: 6827		\$50.00		
Cost per installed bag of Ardex brand SD-P (20 lb. bag) or equivalent COUNTY ID: 6828		\$60.00		

BRAZORIA COUNTY CONTRACT SHEETS

SUPPLY AND INSTALLATION OF CARPET AND FLOORING (CONTINUED)

6.0 Removal of existing floor to include demolition and disposal of:	PRICE PER SQUARE FOOT
Carpet removal for new replacement, cost per square foot: COUNTY ID: 7771	\$0.28
VCT removal for new replacement, cost per square foot: COUNTY ID: 6830	\$0.40
Availability of Product	PATCRAFT HOMEROOM II
Number of days shipment can be made in after receipt of order.	5
Number of days installation can occur within after receipt of order.	1

PRODUCT SPECIFICATIONS FOR CARPET

- 2.1 Style: **I0127 Patcraft Homeroom II 26 Modular or Equivalent**
- 2.2 **Product Specifications**
- | | |
|-------------------------|---------------------------|
| Construction | Textured Loop |
| Fiber Type | Eco Solution Q® Nylon |
| Dye Method | 100% Solution Dyed |
| Gauge | 1/8 |
| Stitches Per Inch | 9.0 |
|
 | |
| Tufted Pile Height | 4/32" low - 6/32" high |
| Tufted Yarn Weight | 26.0 |
| Finished Pile Thickness | 0.129 |
| Tile Size | 24" x 24" |
| Density | 7256 |
| Weight Density | 188,656 |
| Pattern Repeat | None |
| Protective Treatments | SSP® Shaw Soil Protection |
| Primary Backing | non-woven synthetic |
| Secondary Backing | EcoWorx® Tile |
- 2.3 **Performance Specifications**
- | | |
|--------------------------|------------------|
| Radiant Panel | Class I |
| NBS Smoke | Less Than 450 |
| Electrostatic Propensity | Less Than 3.5 kV |
- 2.4 **Materials**
- | | |
|--|-------------------------------|
| Face Fiber | nylon 6 |
| Dye Method | 100% Solution Dyed |
| Backing | polyolefin composite |
| Surface Treatments | non c8 fluorocarbon chemistry |
| does not contain PVC,
phthalates, or PBD/PBDE | |

BRAZORIA COUNTY CONTRACT SHEETS

Recycled Content
Total Recycled Content
(by weight) 44.5 %
Pre-Consumer 32.0 %

2.5 Environmental

MBDC Cradle to Cradle Silver Certified
NSF 140 Platinum Certified
CRI Green Label Plus Certified GLP9968
Singapore Green Label Certified 039-003
Recyclability 100% recyclable
Shaw Closed Looped
Recycling Materials 100.0%

2.6 **Warranty** Lifetime Commercial Limited

2.7 **Color:** Brazoria County to choose

PRODUCT SPECIFICATIONS FOR VINYL

3.1 **Armstrong Excelon 1/8" gauge, Commercial grade or Equivalent**

3.2 Form(s): Tile 12 in (305 mm) Wide x 12 in (305 mm) Length.

Reference Specs: ASTM F 1066 Class 2 – through pattern. Meets requirements for size, thickness, squareness, indentation, impact, dimensional stability, and resistance to chemicals.

3.3 Fire Test Data: ASTM E 648 Critical Radiant Flux Class I – 0.45 or more watts/cm²

ASTM E 662 smoke developed 450 or less numerical flammability ratings alone may not define the performance of the product under actual fire conditions. These ratings are provided only for use in the selection of products to meet the specified limits.

3.4 Static Load Limit: ASTM F 970 75 psi

3.5 Color: Brazoria County to choose

3.6 **Azterra Azrock Collection, 1/8" gauge, Commercial Grade or equivalent**

3.7 Form(s): Tile 12 in (305 mm) Wide x 12 in (305 mm) Length.

Reference Specs: ASTM F 1066 Class 2 – through pattern. Meets requirements for size, thickness, squareness, indentation, impact, dimensional stability, and resistance to chemicals.

3.8 Fire Test Data: ASTM E 648 Critical Radiant Flux Class I – 0.45 or more watts/cm²

ASTM E 662 smoke developed 450 or less numerical flammability ratings alone may not define the performance of the product under actual fire conditions. These ratings are provided only for use in the selection of products to meet the specified limits.

3.9 Static Load Limit: ASTM F 970 400 psi

3.10 Color: Brazoria County to choose

BRAZORIA COUNTY CONTRACT SHEETS

ROPPE RUBBER STAIR TREAD SPECIFICATIONS

- 4.1 Raised, circular, Vantage design or Equivalent
- 4.2 Quality: Rubber treads are made from a specially formed, compressed molded, high-grade synthetic rubber compound.
- 4.3 Durability: Color is inherent throughout every tread, assuring lasting beauty. Added 3 extra thickness in high-wear areas for longer tread life.
- 4.4 Comfort/Noise Reduction – treads cushion every step and help reduce indoor traffic noise
- 4.5 #98 Vantage Profile without riser
- 4.6 Depth: 12" (304.8mm) 3/64" (1.19mm) raised design
- 4.7 Thickness: 3/16" tapering to 1/8" (4.76mm to 3.175mm)
- 4.8 Nose Type: Square
- 4.9 All rubber treads: Conform with U.S. Federal Specification No. RR-T-650C, Composition A, Types 1, 2 and 4
- 4.10 ADA: Roppe rubber stair treads comply with Americans with Disabilities Act regulations
- 4.11 NFPA: Meets flammability requirements of the National Fire Protection Association Life-Safety Code 101
- 4.12 ANSI: Meets building code standards from American National Standards Institute
- 4.13 Color: Brazoria County to choose

ROPPE RUBBER LANDING TILE SPECIFICATIONS

- 5.1 **996 Raised Circular Vantage Design or Equivalent**
- 5.2 Thickness: 11/64" (4.37mm) with profile 1/8" (3.175mm) without profile
- 5.3 Profile height: 3/64" (1.19mm)
- 5.4 Profile diameter: 1-3/32" (27.78mm)
- 5.5 Wear resistance for high traffic areas.
- 5.6 Resists scuffing, gouging, cigarette scorching, most chemicals and common substances.
- 5.7 Dimensionally stable (won't shrink or separate).
- 5.8 Provides underfoot comfort while reducing noise.
- 5.9 Non-conductive – ideal for high traffic areas.
- 5.10 All rubber tile: Conforms to ASTM F-1344-00
- 5.11 Abrasion: ASTM D-3389 (H-18 Calibrau, 500g/load), Wt. loss g/1000 cycles = less than .60g
- 5.12 Hardness: ASTM D-2240, Shore A, 85-90
- 5.13 Tensile strength: ASTM D-412, 1200-1400 psi
- 5.14 Elongation: ASTM D-412, 120%-140%
- 5.15 Slip resistance: ASTM D-2047-75, rated .75 static coefficient of friction, James Machine
- 5.16 Fire resistance: ASTM E-648, radiant panel test, .94 w/cm²
- 5.17 Flamespread: ASTM E-162, index of 45
- 5.18 Color: Brazoria County to choose

ROPPE 700 SERIES THERMOPLASTIC RUBBER BASR OR EQUIVALENT

- 6.1 Colors are inherent throughout base
- 6.2 Exclusive low-gloss satin finish resists scuffing, gouging and most chemicals.
- 6.3 Ribbed back for positive adhesion.
- 6.4 4" installed, style B cove base

BRAZORIA COUNTY CONTRACT SHEETS

6.5 Color: Brazoria County to choose

ADHESIVE

- 7.1 Adhesive products shall be same brand as manufacturer's product (i.e. Armstrong adhesive for Armstrong tile).
- 7.2 Premium adhesive products shall be required for all products. Product submittals must be approved by Brazoria County prior to their application.

MISCELLANEOUS INSTRUCTIONS

- 8.1 All installation cost shall be included in the bid price. All manufacturers installation procedures and guidelines shall be followed.
- 8.2 The vendor shall be responsible for acceptance of floor conditions and for proper floor preparations prior to product installations. All cost associated with floor preparations shall be the Vendors responsibility. Vendor shall include up to three ten (10) pound bags of Ardex SD-F cementitious floor patch material and included in the bid cost. Additional floor patch and float preparations will be at additional cost per installed bag.. Ardex brand of floor patch, either SD-F(10 lb.), SD-P (20 lb.) or equivalent, shall be used for all required floor preparations.
- 8.3 All products and accessories required for proper installations shall be included in the bid price.
- 8.4 Rubber floor transitions shall be used where applicable.
- 8.5 Vendor shall be responsible for the actual required material quantities. Quantity amounts listed are for bid comparison only. Vendors shall verify quantities before ordering. Invoices to Brazoria County shall indicate actual material quantities used at the job site, billed at the unit price, not to exceed the estimated quantities listed in the bid documents.
- 8.6 Vendor shall be responsible for the removal, demolition and disposal of existing floor coverings, as in carpet replacement or VCT removal for new replacement tiles. Brazoria County will be responsible for the removal of furniture as needed.